

## C/TT-600 SOFTWARE-DEFINED RADIO

### Modular, multiband software-defined radio

L3Harris' C/TT-600 is a modular, multiband software-defined radio with a flexible parts program designed to support a wide range of applications and orbits including LEO, MEO, GEO, Cislunar and deep space. Designed with the user in mind, C/TT-600's "sliced" architecture approach enables selection of a variety of configurations which can be purchased off-the-shelf or customized for unique mission requirements.



#### BACKGROUND

C/TT-600 is the culmination of over 60 years of design experience providing UHF-, S-, X- and Ka-band high reliability, mission-critical communications equipment for spacecraft applications spanning LEO to deep space. C/TT-600 is derived from high-TRL radio designs with spaceflight heritage and is specifically tailored to meet the demands of the Artemis generation.

#### MODULARITY AND FLEXIBILITY

The modular design consists of a base power supply and digital processing module forming the base radio. RF band conversion modules attach to the base radio, providing frequency agility within a desired band. C/TT-600 is designed with architecture flexibility in mind, including support for external power and low noise amplifiers. C/TT-600 also provides internal SSPA options for UHF- and S-band.

#### MULTI-ORBIT PRODUCT SERIES

Designed with flexible parts program to support multiple orbits:

- > LEO
- > MEO
- > GEO
- > Cislunar
- > Deep space (coming soon)

#### NETWORKS

Designed to support new and legacy network standards:

- > Near Space Network (NSN) and LunaNet
- > Ground Network (GN)
- > Deep Space Network (DSN)
- > TDRSS SA/MA standards (450-SNUG)
- > CCSDS standards
- > C2V2 mode (NASA SSP-50934)
- > And more

#### KEY FEATURES AND BENEFITS

Designed to support new and legacy network standards:

- > Software-defined radio with modular and flexible design
- > RF band conversion support UHF, S, X, Ka and others
- > Flexible parts program supports multiple orbits
- > On-orbit reconfigurable radio
- > On-orbit frequency agility within a band
- > Transparent/regenerative ranging
- > Optional embedded AES-256 encryption
- > Planned product lifecycle capability updates
- > Derived from high-TRL heritage products C/TT-520, C/TT-524, T-748, T-751, Electra-Lite, Universal Space Transponder



## C/TT-600

A MODULAR, MULTIBAND  
SOFTWARE-DEFINED RADIO

#### APPLICATIONS

- > TT&C
- > RPO and docking
- > Mission data
- > Intersatellite relays
- > EVA communications
- > Surface operations



Image Credit: NASA



Image Credit: NASA



(SSPA not included in above images)

TRANSMITTER	UHF-BAND	S-BAND	X-BAND	KA-BAND
Center Frequency	390 – 450 MHz	2200 – 2300 MHz	8025 – 8500 MHz	25.25 – 27.5 GHz
Frequency Stability	+/- 2 ppm (TBR)			
Phase Noise	TBD	TBD	TBD	TBD
EVM	< 9% (TBR)			
Data Rate	Up to 12 Mbps	Up to 6 Mbps	Up to 200 Mbps	Up to 1 Gbps
Modulation	CPFSK, BPSK, QPSK	BPSK, (O)QPSK, SQPN, SS-UQPSK, PM/BPSK, PCM/PM/PSK	BPSK, (O)QPSK, 8-PSK, 16-APSK	BPSK, (O)QPSK, 8-PSK, 16-APSK

RECEIVER	UHF-BAND	S-BAND	X-BAND	KA-BAND
Center Frequency	390 – 450 MHz	2025 – 2110 MHz	7145 – 7235 MHz	22.55 – 23.55 GHz
Data Rate	Up to 10 Mbps	Up to 3 Mbps	Up to 100 Mbps	Up to 600 Mbps
Modulation	CPFSK, BPSK, QPSK	SQPSK, (SS-)BPSK, SS-UQPSK, PM/BPSK, PCM/PM/PSK, SQPN	BPSK, (O)QPSK, 8-PSK	BPSK, (O)QPSK, 8-PSK
Tracking Rate/Range	TBD	TDRSS & C2V2; 70 Hz/s (125 bps); 380 Hz/s (>1 kbps); GN; 35 kHz/s	TBD	TBD
Input RF Signal	-130 dBm to -70 dBm	-137 dBm to -17 dBm	TBD	TBD

TRANSCEIVER	UHF-BAND	S-BAND	X-BAND	KA-BAND
Mission Life	Up to 10 years (parts grade scalable to mission)			
Parts Grade	EEE-INST-002 Level 2 (parts grade scalable to mission)			
Radiation	C/TT-600 Base: 50 kRad(Si); 44 MeV-cm <sup>2</sup> /mg SEL LET (supports operation in LEO) C/TT-600 Hardened: 100 kRad(Si); 75 MeV-cm <sup>2</sup> /mg SEL LET (supports operation in MEO/GEO/CISLUNAR)			
Fatigue Lifetime	100,000 cycles			
Bus Voltage	+22 V to +36 VDC			
EMC/EMI	MIL-STD-461F (tailored)			
Data/Clock Interface	RS-422, LVDS, Gigabit Ethernet			
Control/Status Interface	RS-422, Gigabit Ethernet			
DC Power	< 15 W	< 15 W	< 45 W	< 45 W
Dimensions (LxWxH)	< 9 L x 5 W x 5 H in	< 9 L x 5 W x 5 H in	< 9 L x 7 W x 5 H in	< 9 L x 7 w x 6 H in
Mass	< 7 lbs	< 7 lbs	< 9 lbs	< 12 lbs

SSPA	UHF-BAND	S-BAND	X-BAND	KA-BAND
RF Output Power	8.5 W	20 W	12 W	1 W
DC Power	< 25 W	< 70 W	< 75 W	< 25 W
Operating Temp	-34°C to +70°C			
Dimensions (LxWxH)	< 9 L x 2 W x 5 H in	< 9 L x 2 W x 5 H in	< 8 L x 8 W x 3 H in	< 4 L x 5 W x 2 H in
Mass	< 5 lbs (TBR)	< 5 lbs (TBR)	< 5 lbs (TBR)	< 5 lbs (TBR)

Notes: Product currently in development. Specifications are estimates and subject to change. Additional C/TT-600 product configurations and custom requests available upon inquiry. Export classifications may vary.

### C/TT-600 Software-Defined Radio

© 2024 L3Harris Technologies, Inc. | 08/2024 | L26495

**NON-EXPORT CONTROLLED:** THIS DOCUMENT CONSISTS OF INFORMATION THAT IS NOT DEFINED AS CONTROLLED TECHNICAL DATA UNDER ITAR PART 120.33 OR TECHNOLOGY UNDER EAR PART 772.

L3Harris Technologies is the Trusted Disruptor in the defense industry. With customers' mission-critical needs always in mind, our employees deliver end-to-end technology solutions connecting the space, air, land, sea and cyber domains in the interest of national security. Visit [L3Harris.com](https://www.l3harris.com) for more information.



1025 W. NASA Boulevard  
Melbourne, FL 32919

[L3Harris.com](https://www.l3harris.com)